



ENVIRONMENTAL PROTECTION PRODUCTS AND THERMAL BARRIERS For A Green World

ARMATEX® CF 10 CARGOTEX PLUS

ARMATEX® CF 10 CARGOTEX PLUS is a fiberglass fabric impregnated with our state-of-the-art polymeric coating. Designed primarily for thermal insulation and high temperature applications, ARMATEX® CF 10 CARGOTEX PLUS is suitable for indoor use. The use of a fiberglass base fabric creates a product that is highly flame-resistant with high tensile strength and superior dimensional and thermal stability.



AVERAGE PHYSICAL PROPERTIES

Coating	Cargotex Plus
Color	White, special colors available upon request
Thickness, inches, nominal	0.007
Temperature Rating	
Base Fabric	1000°F • 538°C
Coating	450°F • 232°C, transient exposure 600°F • 315°C
Weight, oz/sy, nominal	10
Tensile Strength, lbs/in, nominal	250 x 200 (warp x fill)
Width, inches	38, 42, 60 (+/- 5%)
Standard Roll Size	50 LY

Tolerance is +/- 10% unless otherwise stated.

The technical data presented herein are indicative of representative properties and are intended as a specification guide only. No warranties are expressed or implied as application conditions are beyond our control.

Rev.1.5-20.2019